

ScaleGone™ – Solid Slow Release Scale Inhibitor

Features

ScaleGone™ is designed to be placed along with proppant, **delivering scale inhibitors where they are needed the most!** ScaleGone technology delivers **long-term protection from scale build-up** using a threshold inhibitor which is effective against oilfield scales like calcium carbonate, calcium sulfate, strontium and barium sulfate. It also aids in preventing precipitation of naturally occurring radioactive material (NORM) waste.

Applications

ScaleGone™ inhibitor is recommended for use in wells with BHT of up to 280 °F.


Compatibility

ScaleGone™ inhibitor is compatible with all known aqueous fracturing fluids including slickwater, linear and cross-linked gels.

Benefits

ScaleGone™ provides a **steady source of scale inhibitor for years**, greatly **reducing operating cost** and **maintaining optimum production**. ScaleGone™ can be **added on the fly** with proppant, eliminating the need for a separate treatment. ScaleGone™ is a **high active content** composite, greater than 60% w/w of the product is active material. ScaleGone™ leaves **no residue in the proppant pack**. Other long-term inhibitors leave behind insoluble residue like polymers, silica or diatomaceous earth, reducing proppant pack conductivity.

ScaleGone™ Sales	
Form	Solid
Specific	1.05
pH	6.5-
Flash	0 230
DoT	Not
Packagi	As



Dynamic Scale Loop Testing

